

PUMP START RELAY

1500 SERIES



The Pump Start Relay enclosure is constructed with a Corrosion, UV and flame retardant resistant shockproof material.

- **Standard, rain, tight, secure, rustproof and flame retardant enclosure** – provides a safe and secure connection in an enclosure that will last a lifetime.
- **U.L. rated relay** – ensures that the relays are approved for its intended use.
- **Large easy access enclosure** – provides easy accessibility during wiring.
- **Enclosure has versatility installation** – provides for easy connections.
- **110 VAC or 24 VAC coils available** – provides for a variety of applications up to 7.5 HP.
- **2 year warranty** – factory support up to two years after purchase.



K-Rain Manufacturing Corp.

1640 Australian Avenue

Riviera Beach, FL 33404 USA

561.844.1002

FAX: 561.842.9493

1.800.735.7246 | www.krain.com

Models

<p>1510 Coil Specifications 120V AC, 60 Hz Inrush: 35 VA Sealed: 7.0 VA Resistance ($\pm 10\%$): 250 OHMS</p> <p>Mini Coil 24V AC, 50/60 Hz Inrush: 52 mA</p>	<p>Double Pole, Single Throw Inductive: 20 AMP Resistive: 30 AMP Input: 120V AC - up to 2 H.P. UL Rated</p> <p>Sealed: 1.2 VA Resistance ($\pm 10\%$): 155 OHMS</p>
<p>1520 Coil Specifications 240V AC, 60 Hz Inrush: 35 VA Sealed: 7.0 VA Resistance ($\pm 10\%$): 1000 OHMS</p> <p>Mini Coil 24V AC, 50/60 Hz Inrush: 52 mA</p>	<p>Double Pole, Single Throw Inductive: 20 AMP Resistive: 30 AMP Input: 240V AC - up to 3 H.P. UL Rated</p> <p>Sealed: 1.2 VA Resistance ($\pm 10\%$): 155 OHMS</p>
<p>1521 Coil Specifications 120V AC, 60 Hz Inrush: 42 VA Sealed: 8.5 VA, 3.6 Watts Resistance ($\pm 10\%$): 210 OHMS</p>	<p>Double Pole, Single Throw Inductive: 20 AMP Resistive: 30 AMP Input: 120V AC - up to 3 H.P. 240V AC - up to 3 H.P.</p>
<p>1522 Coil Specifications 24V AC, 60 Hz Inrush: 35 VA Sealed: 7 VA, 3 Watts Resistance ($\pm 10\%$): 11 OHMS</p>	<p>Double Pole, Single Throw Inductive: 20 AMP Resistive: 30 AMP Input: 120V AC - up to 3 H.P. 240V AC - up to 3 H.P.</p>
<p>1551 Coil Specifications 120V AC, 60 Hz Inrush: 77 VA Sealed: 10 VA, 4 Watts Resistance ($\pm 10\%$): 89.5 OHMS</p>	<p>Double Pole, Single Throw Inductive: 40 AMP Resistive: 50 AMP Input: 120V AC - up to 3 H.P. 240V AC - up to 5 H.P.</p>
<p>1552 Coil Specifications 24V AC, 60 Hz Inrush: 60 VA Sealed: 7 VA, 2.3 Watts Resistance ($\pm 10\%$): 5.61 OHMS</p>	<p>Double Pole, Single Throw Inductive: 40 AMP Resistive: 50 AMP Input: 120V AC - up to 3 H.P. 240V AC - up to 5 H.P.</p>
<p>1553 Coil Specifications 24V AC, 60 Hz Inrush: 60 VA Sealed: 7 VA, 2.7 Watts Resistance ($\pm 10\%$): 5.61 OHMS</p>	<p>THREE PHASE OPERATION Triple Pole, Single Throw Inductive: 40 AMP Resistive: 50 AMP Input: 120V AC - up to 3 H.P. 240V AC - up to 10 H.P.</p>

Dimensions

- Height: 7.25"/14.5 cm
- Width: 6.25"/11.4 cm
- Depth: 3.875"/6.1 cm

