

PRO-LC

WiFi-Ready Irrigation Controller



The Pro-LC Controller is designed for residential and light commercial applications.

Feature-packed, user-friendly and now a WiFi-ready controller.

The PRO-LC is available in 4, 8 and 12 stations and in indoor and outdoor models. Add the new 3100-BRIDGE (sold separately) and this feature-packed controller can be managed from your smart device using WiFi technology. Other user-friendly features:

- Easy to follow programming
- A full program screen display listing watering days, number of start times, number of stations and special programming
- Large LCD display; rain/freeze sensor compatibility
- Lighting feature allows you to create a start time and run time to operate a lighting system.
- Weather IQ® uses local weather conditions to bypass the irrigation schedule in wet conditions
- Seasonal adjust for water conservation
- A buried valve locator for easy maintenance



Bridge WiFi Module



K-Rain Manufacturing Corp.
1640 Australian Avenue
Riviera Beach, FL 33404 USA
561.844.1002
FAX: 561.842.9493

1.800.735.7246 | www.krain.com



Features and Benefits

- Easy to follow programming
- Large LCD display
- Patented full program display feature shows watering days, number of start times, number of stations and special programming
- Rain sensor and rain/freeze sensor ready – Allows automated operation to be controlled by sensor station by station.
- Lighting feature allows you to create a start time and run time to operate a lighting system.
- Weather IQ® uses local weather conditions to bypass the irrigation schedule in wet conditions
- Seasonal adjust
- Buried valve locator
- Built-in Level – Makes leveling the unit easy

Models

OUTDOOR MODELS

3104W	4 station, 110V AC internal transformer
3104W-P	4 station, 110V AC internal transformer with pigtail
3104W-220	4 station, 220V AC internal transformer
3108W	8 station, 110V AC internal transformer
3108W-P	8 station, 110V AC internal transformer with pigtail
3108W-220	8 station, 220V AC internal transformer
3112W	12 station, 110V AC internal transformer
3112W-P	12 station, 110V AC internal transformer with pigtail
3112W-220	12 station, 220V AC internal transformer

INDOOR MODELS

3104WID	4 station, 110V AC plug pack transformer
3104WID-220	4 station, 220V AC plug pack transformer
3108WID	8 station, 110V AC plug pack transformer
3108WID-220	8 station, 220V AC plug pack transformer
3112WID	12 station, 110V AC plug pack transformer
3112WID-220	12 station, 220V AC plug pack transformer

Specifications

OPERATING SPECIFICATIONS

- Station Run Times:
1 minute to 6 hours
- Number of Programs: 3
- Number of Automatic Start Times:
4 per program
- Program Watering Schedules:
Odd (odd calendar days),
Even (even calendar days),
Custom (day of the week)

ELECTRICAL SPECIFICATIONS

- Power Input:
110V AC, 50/60Hz
240V AC, 50/60Hz
- Power Output: 24V AC 1.0Amp
- Power Backup: Lithium coin-cell battery maintains time and date during primary power outages.

DIMENSIONS

- Height: 7" (17,8 cm)
- Width: 7" (17,8 cm)
- Depth: 3.5" (8,9 cm)

ACCESSORIES

- 3100-BRIDGE
WiFi Module
- 3208-HRS
Hardwired Rain Sensor
- 3208-HRFS
Hardwired Rain/Freeze Sensor
- 3208-UWRFS
Universal Wireless Rain/Freeze Sensor