



- ① FINISH GRADE
- ② STANDARD VALVE BOX
- ③ 18-24 INCH LINEAR LENGTH OF 2-WIRE PATH COIL WITH DBR/Y-6 WATERPROOF CONNECTORS (2)
- ④ SCHEDULE 80 NIPPLE, LENGTH AS REQUIRED
- ⑤ 2-WIRE JACKETED DECODER CABLE, SIZED PER SPECIFICATIONS
- ⑥ RED AND BLACK WIRES FROM DECODER MODULE TO 2-WIRE PATH
- ⑦ K-RAIN SITEMASTER SENSOR DECODER MODEL 3408: SECURE WITH ZIP TIES TO 3/4" SLEEVE, ATTACH TO 1/2" PVC STAKE
- ⑧ YELLOW CONTROL WIRE TO FLOW SENSOR WITH WATERPROOF CONNECTORS (2)
- ⑨ REDUCER AS REQUIRED (2)
- ⑩ BRICK SUPPORTS (4)
- ⑪ 6" DEPTH OF 3/4" WASHED GRAVEL
- ⑫ K-RAIN 1-1/2" FLOW SENSOR MODEL FS228-15

00 K-RAIN SITEMASTER: FLOW SENSOR DECODER

3" = 1'-0"