



- 1) FINISH GRADE
- (2) STANDARD VALVE BOX
- (3) 18-24 INCH LINEAR LENGTH OF CONTROL WIRE WITH WATERPROOF CONNECTORS AND ZONE ID TAG: FOR 9V DC LATCHING SOLENOID CONNECT BLACK WIRE TO COMMON AND RED WIRE TO STATION WIRE
- 4 IRRIGATION MAINLINE AND FITTINGS PER SPECIFICATIONS
- (5) K-RAIN PROSERIES 100 VALVE
  MODEL 7001-9VDC-SL-NFC:
  REMOTE CONTROL VALVE WITH 1" SLIP
  FITTING AND SELF-CLEANING METERING
  SCREEN, WITHOUT FLOW CONTROL. PROVIDE
  9V DC LATCHING SOLENOID FOR BATTERY
  OPERATED TIMERS
- (6) PVC SCHEDULE 80 NIPPLE
- 7 LATERAL PIPE WITH PVC SCHEDULE 40 ADAPTER
- 8 BRICK SUPPORTS (4)
- 9 6" DEPTH OF 3/4" WASHED GRAVEL

(00)

K-RAIN PROSERIES 100: 1" REMOTE CONTROL VALVE

3" = 1'-0"

www.krain.com