VALVE COMPARISON CHART

Versatile and heavy-duty, ProSeries valves deliver long life and reliable performance. Offering a wide array of features and benefits, the K-Rain line is manufactured with the highest standards and provides exceptional functionality.

	ProSeries 100				ProSeries 150			ProSeries 200		
Item Number	**7075**	**7075**	**7001**	**7001**	**7101**	**7115**	**7102**	**7201**	**7215**	**7202**
Models	FEMALE THREAD, SL, BSP	NFC, SL-NFC, BSP-NFC	FEMALE THREAD, SL, BSP, MXB, MXM, BSP-MXM, BSP	BSP-NFC, MXM-NFC, BSP-MXM -NFC, MXB-NFC	FEMALE THREAD, SL, BSP, J, J-SL, J-BSP, J-MXB	FEMALE THREAD, BSP	FEMALE THREAD, BSP	FEMALE THREAD	FEMALE THREAD	FEMALE THREAD
Specifications										
Size	3/4"	3/4"	1"	1"	1"	1 1/2"	2"	1"	1 1/2"	2"
Flow range (GPM)	.25-35	.25-35	.25-35	.25-35	.25-30	20-120	20-120	5-30	20-100	20-150
Pressure range (PSI)	20-150	20-150	20-150	20-150	10-150	20-150	20-150	6-200	6-200	6-200
Features										
Flow control	•		•		•	•	•	•	•	•
24VAC soleniod	•	•	•	•	•	•	•	•	•	•
Heavy duty, corrosion resistant	•	•	•	•	•	•	•	glass-filled nylon	glass-filled nylon	glass-filled nylon
Tilt diaphragm/ piston assembly	•	•	•	•						
Manual external bleed screw	•	•	•	•	•	•	•			
Manual internal bleed through solenoid	•	•	•	•	•	•	•			
Captured plunger	•	•	•	•	•	•	•	•	•	•
Self-cleaning screen	•	•	•	•						
Removable metering pin					•	•	•			
Removable inlet cap						•	•			
Heavy duty Santoprene® diaphragm	•	•	•	•	•	•	•			
Glass-filled nylon construction and reinforced rubber diaphragm								•	•	•
Sellf-cleaning diaphragm	•	•	•	•						
Water flow indicator	•	•	•	•	•	•	•	•	•	•
Electric or manual operation	•	•	•	•	•	•	•	•	•	•
Options										
9VDC solenoid	•	•	•	•	•	•	•			
BSP inlet & outlet	•	•	•	•	•	•	•	•	•	•