



# Nozzle Comparison Chart



	Rotary Nozzle Series	Fully Adjustable Rotary Nozzle	HE KVF Adjustable Nozzles	KV Nozzles	Fixed Pattern Nozzles
<b>SPECIFICATIONS</b>					
Nozzle Types	Full 360°, Adjustable	Fully Adjustable	High Efficiency, Fully Adjustable	Fully Adjustable	Fixed Spray
Arc	90° - 360°	80° - 360°	0° - 360°	0° - 360°	90° - 360°
Radius	13' - 30'	13' - 29'	9' - 18'	7' - 20'	6' - 17'
Thread	Female	Female	Female	Male	Female & Male
Special Patterns	Right, Left & Side Strip				Center, End, Side & High/Low Strip
Spray Pattern Dimensions	4' x 15' to 7' x 32'				4' x 12' to 15' x 5' x 32'

<b>FEATURES</b>					
Color Coded	•	•	•	•	•
Automatic Matched Precipitation	•	•	•	•	
Warranty	2 Year	2 Year	2 Year	2 Year	2 Year

<b>PERFORMANCE DATA</b>					
Precipitation Square	0.40 - 0.55 in/hr	0.41 - 0.51 in/hr	1.13 - 2.25 in/hr	1.43 - 3.31 in/hr	1.20 - 2.16 in/hr
Precipitation Triangle	0.44 - 0.59 in/hr	0.48 - 0.59 in/hr	1.31 - 2.58 in/hr	1.46 - 3.82 in/hr	1.38 - 2.20 in/hr