

# ROTOR COMPARISON CHART



SPECS	MiniPro	RPS50	RPS75	RPS75i	RPS Select	SuperPro	ProPlus	ProSport
Inlet Size	1/2"	1/2"	3/4"	3/4"	3/4"	3/4"	3/4"	1"
Radius	18'-33'	18'-33'	22'-51'	13'-48'	33'-46'	26'-46'	22'-50'	45'-77'
Flow Range (GPM)	0.8-3.3	0.8-3.3	.75-8.2	0.4-9.7	1.3-6.8	0.5-9.5	0.5-10.0	5.1-32.5
FEATURES								
Pressure Rating (PSI)	20-70	20-70	30-70	30-70	30-70	20-70	20-70	40-90
Nozzle Trajectory	25°	25°	26°	26°	24°	26°	26°	26°
Pre-installed Nozzles	#1.5	#1.5	#3.0	#2.5	4 Built-in Selectable	#2.5	#2.5	#10
Low Angle Nozzle Choices			•	•		•	•	
Non-Strippable Drive (arc memory clutch)						•	•	•
Arc Adjustment Range	40°-360°	40°-360°	40°-360°	40°-360°	40°-360°	40° to Cont. 360°	40° to Cont. 360°	40° to Cont. 360°
Top Arc Set Indication	•				•	•	•	•
Intelligent Flow Technology®				•		•		
Reclaimed Water Available	•		•	•	•	•	•	•
Stainless Steel Available			•	•				•
Optional or Factory Installed CV	•	•	•	•	•	•	•	•
Warranty	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years

## Radius Comparison at a glance

