



- ① FINISH GRADE
- ② REMOTE CONTROL VALVE IN STANDARD VALVE BOX: REFER TO DETAIL
- ③ 18-24 INCH LINEAR LENGTH OF 2-WIRE PATH COIL WITH DBR/Y-6 WATERPROOF CONNECTORS (2)
- ④ GROUNDING WIRE TO GROUND PLATE OR ROD (10 OHMS RESISTANCE OR LESS), INSTALLED PER ASIC GUIDELINES
- ⑤ 2-WIRE JACKETED DECODER CABLE, SIZED PER SPECIFICATIONS
- ⑥ RED AND BLACK WIRES FROM DECODER MODULE TO 2-WIRE PATH
- ⑦ K-RAIN SITEMASTER SURGE PROTECTOR MODEL 3402: SECURE WITH ZIP TIES TO 3/4" SLEEVE, ATTACH TO 1/2" PVC STAKE
- ⑧ K-RAIN SITEMASTER FOUR STATION DECODER MODEL 3406: SECURE WITH ZIP TIES TO 3/4" SLEEVE, ATTACH TO 1/2" PVC STAKE
- ⑨ YELLOW IRRIGATION CONTROL WIRE TO VALVE SOLENOIDS WITH ID TAGS (4) AND WATERPROOF CONNECTORS (8): MAXIMUM LENGTH 100 FEET