Pro EX 2.0 WiFi 💹 Enabled Controller

QUICK START GUIDE

Connecting the WiFi hub to the internet



Includes: Instructions for Ó Apple iOS

Sharing controller with contractor

Adding controllers to homeowner and contractor accounts



START HERE FOR iOS APP



ITEMS NEEDED:

- 1. Pro Ex 2.0 WiFi Enabled Irrigation Controller
- 2. RF Module
- 3. WiFi Hub

Powering and Placing your WiFi Hub:

A) Pick a dry location inside the home or in the garage with good WiFi signal strength. An easy way to evaluate signal strength is using the WiFi signal indicator on your smartphone or tablet; the icon should be full. **Do not place hub next to large metal appliances, e.g. hot water heater, air conditioning unit, etc.



B) After plugging the power to the WiFi Hub, the "K" LED light should be flashing (On/ Off). This may take several seconds.



NOTE: If the LED is not flashing, reset the hub using the setting button located on the bottom base of the unit. The "K" LED should start flashing (On / Off) after holding down the button for three seconds.



Creating a User Account and Connecting the Wifi Hub to the Controller for the first time using an iOS Device:

STEP 1

Download the K-Rain Pro EX WiFi App From the itunes App Store.





Click on "Create Account" Button.



STEP 3

Enter a valid e-mail address. **NOTE:** Password must be at least 6 characters long.

và	
	Line Brant
	Lose Dente Personal

STEP 4

Enter user information. **NOTE:** Smartphone or tablet MUST be connected to the WiFi network in order to connect the WiFi Hub.

< Back	User Information	Next
1	User	
Fighters.		
taj: Inited		
for summer to	(BIE	
	Address	
Aldense		
ыlı,		
there (Printog	e :	
-coality.		
DP (Post) Ar	(1) 乾	

STEP 5

Reminder screen. After following procedure indicated, click Next.

		Add	Cor	troll	er.	Carros
		C	Get Ar	sady		
Maki	r surie pit,	your H Oderd	(Auro In und	migati; power	in clim) ed on	roller is
Ma	ke sun p	your Ngge	i K-Rain d in an	d prim	tub dei Mect	kæis.
74	ate Th	e litur	Topin :	though	be flat	hing
If is in	nt Hater	ung, p	reas d	he SET	INGB	utton for
			3 9500	0.01		
			Ner	ecn.		
		Add	Nei	nt nt	pr	Cunter
		Add	Ner Ner Com	ntroll	et i	Cuncu
	FOR	Add	Nei Com L-BAN	ect ND RO	er	Cança
MAKE	F08	Add DUA YOU	I Con Conn L-BAN R SM	ect ARTP H2 WI	er UTERS HONE/ FI NET	Cancer TABLET WORK
MAKE 16 DO	FOR SUFII	Add DUA YOU d to a	I Con Com L-BAN R SM R SM S 2 40 MCE 8 SHz W	ect ARTP H2 VA S NOT	er UTERS HONE/ FINET COMP nals	Cancer TABLET WORK ATIBLE

STEP 6 Connect app to K-Rain WiFi network.*



***NOTE:** For dual-band routers, make sure your smartphone/tablet is connected to a 2.4GHz WiFi Network. This device is not compatible with 5GHz WiFi signals.

Connecting your controller to the WiFI Hub:

STEP 7

Go to the Pro Ex 2.0 controller faceplate. Move the dial to the REMOTE/PIN location.



Press UP button until you see NO WiFi on controller LCD.

Press MANUAL START/NEXT button and it will start searching for the WiFi Hub.

When the display shows "YS WiFi" on the _ LCD, it has been paired with the WiFi Hub.



STEP 8

Go back to K-Rain Pro EX 2.0 WiFi Controller App. It will show this screen as a reminder that the Controller and WiFi hub had to be paired before going to the next step.



Connecting your WiFi Hub to your Router:

STEP 9

Enter home network WiFi Network (SSID) and password. Click configure controller.

6	Add Controller	Cuntur
	Connect to K-Rain WIFI Hub	
Ente	r the name (SSE) and password bome WIFI network.	l for your
WPS 8	Network Netter	ũ.
W.F. J	exword	
	Show Password	CI)
	Configure Controller	

Confirmation Screen. Wait a few minutes for the WiFi Hub to connect to the Cloud. At this point, the blue light on Hub should stop flashing and become solid. If blue light is not solid, has gone out or still flashing, click "Try Again", follow instructions.



TROUBLESHOOTING GUIDE

LED Indication	BLUE	GREEN	RED
ACCESS POINT (AP) Mode: WiFi Hub is on AP mode (for device setup).	Flashing	OFF	OFF
RF Communication OK: WiFi Hub Authenticating with user WiFi Router.	OFF	Flashing	OFF
RF Communication OK: WiFi connected to local user router successfully. Pending to connect to K-Rain server.	OFF	ON	OFF
RF Communication OK: WiFi connection to web server OK.	ON	OFF	OFF
RF Communication Error: Momentary or constant inadequate RF communication.	OFF	OFF	ON

STEP 11

Name your controller, and complete the address location. Click next.

Casek Controller Information Next
Controller Information
Controller Teams
Address
00s
Dere / Emission
Courte
pur demonstration
Station Names
1 Station 1
2 Ithioco 2
3 Stolog 3
4 372900 il

NOTE: It is important to completely fill in address for Weather Forecast and **Weather IQ™** accuracy.

STEP 12

Congratulations on connecting your WiFi controller. Click DONE.



For additional support, please visit: **support.krain.com/support/home**

START HERE FOR ANDROID APP



ITEMS NEEDED:

- 1. Pro Ex 2.0 WiFi Enabled Irrigation Controller
- 2. RF Module
- 3. WiFi Hub

Powering and Placing your WiFi Hub:

A) Pick a dry location inside the home or in the garage with good WiFi signal strength. An easy way to evaluate signal strength is using the WiFi signal indicator on your smartphone or tablet; the icon should be full. **Do not place hub next to large metal appliances, e.g. hot water heater, air conditioning unit, etc.



B) After plugging the power to the WiFi Hub, the "K" LED light should be flashing (On/ Off). This may take several seconds.



NOTE: If the LED is not flashing, reset the hub using the setting button located on the bottom base of the unit. The "K" LED should start flashing (On / Off) after holding down the button for three seconds.



Creating a User Account and Connecting the Wifi Hub to the Controller for the first time using an Android Device:

STEP 1

Download the K-Rain Pro EX WiFi App From the Google Play App Store.





NOTE: From the Settings Menu on your device, grant "all permissions" after downloading app.

Click on "Create" Button. **NOTE:** Password must be at least 6 characters long.

Login	
Account	Account eMde
Password :	Pecount Paseward

STEP 4

Enter user information **NOTE:** Smartphone or tablet MUST be connected to the WiFi network in order to connect the WiFi Hub.

📕 K-Fain	10	1	LEGAL
<u>6</u>	8	÷ợ:-	°
1	User		÷
First Name			
Last Name			
Cell Number f	or SMS		
Show wind s	peed	MPH	KM/HR
Show tempe	rature	(TP)	t
Us	er Addi	ress	
City			
State / Provins			
Country			
ZIP / Postal O	ale		

STEP 3

Enter a valid e-mail address

Login	\bigcirc
Account	Account eMue
Password :	Necount Paseword
Repeat :	Repeat Password
C	ANCEL

STEP 5

Reminder screen. Enter user information. After following the procedure indicated, click Next.*

Add Controller	CANCEL
Get Ready	
Make sure your K Rain Inlgation plugged in and power	on controller is ed on
Make sure your K-Rain WiFi plugged in and pow	Hub device in ered
Note: The Blue aght should If is not flashing, press the SET 3 seconds	be flashing. TING button for
NEXT	-
Add Controller	CANCEL
FOR DUAL-BAND F	OUTERS
MAKE SURE YOUR SMARTPH connected to a 2.4GHz WIF	ONE/TABLET IS I NETWORK
NOTE -THIS DEVICE IS NOT CO 50Hz WIFI signa	MPATIBLE WITH
NEXT	

***NOTE:** For dual-band routers, make sure your smartphone/tablet is connected to a 2.4GHz WiFi Network. This device is not compatible with 5GHz WiFi signals.

Connecting your controller to the WiFI Hub:

STEP 6

Go to the Pro Ex 2.0 controller faceplate. Move the dial to the REMOTE/PIN location.

Press UP button until you see NO WiFi on controller LCD. -

Press MANUAL START/NEXT button and it will start searching for the WiFi Hub.

When the display shows "YS WiFi" on the LCD, it has been paired with the WiFi Hub.

STEP 7

Go back to K-Rain Pro EX 2.0 WiFi Controller App. It will show this screen as a reminder that the Controller and WiFi hub had to be paired before going into the next step.



Connecting your WiFi Hub to your Router:

NO WIFT

FINDING

YS WIFI

STEP 8

Enter your home network WiFi Network (SSID) and password. Click configure controller.



Confirmation Screen. Wait a few minutes for the WiFi Hub to connect to the Cloud. At this point, the blue light on Hub should stop flashing and become solid. If blue light is not solid, has gone out or still flashing, click "Try Again", follow instructions.

TROUBLESHOOTING GUIDE

LED Indication	BLUE	GREEN	RED
ACCESS POINT (AP) Mode: WiFi Hub is on AP mode (for device setup).	Flashing	OFF	OFF
RF Communication OK: WiFi Hub Authenticating with user WiFi Router.	OFF	Flashing	OFF
RF Communication OK: WiFi connected to local user router successfully. Pending to connect to K-Rain server.	OFF	ON	OFF
RF Communication OK: WiFi connection to web server OK.	ON	OFF	OFF
RF Communication Error: Momentary or constant inadequate RF communication.	OFF	OFF	ON

STEP 10

Name your controller, complete address location of this controller. Click next.

	Q 1 1 3	3:26	PM
te investor	Controlle	rs	
Controller	lamé		
Co	ntroller Ad	dress	
CRV			
State / Pro	ilinoe:		
Country			
JIP / Poeta	Code		
Ť.	Station	8	
1 Station	1		
\triangleleft	0		

NOTE: It is important to completely fill in the address for Weather Forecast and **Weather IQ™** accuracy.



STEP 11

Congratulations on connecting your WiFi controller. Click DONE.



For additional support, please visit: support.krain.com/support/home

HOW TO SHARE CONTROLLER

CONTRACTOR Adding a Pro Ex 2.0 WiFi Controller to Your Account

Register for a professional account at: www.krain.com/proexcontractor

NOTE: The homeowner must enable the share feature via their account prior to adding a controller to the contractor's account.

Ask the homeowner to complete the contractor information card included for you.

WEBSITE METHOD:

To add a controller via web browser (MAC address): Go to **myproex.krain.com** and login. Select "My Account" page. Enter MAC Address printed on WiFi Hub and Click ADD. Refresh Screen.

The controller should now appear. MANAGE allows you to log into that controller and modify settings.

If controller does not appear, contact the homeowner and ask them to share via the instructions provided.

FROM NATIVE iOS/ANDROID App:

You should receive an email **from the homeowner** with an attachment. If you have the App installed, simply tap on the attachment to install:

If you do not receive the email, please check spam and then contact the homeowner.

	My	account details
Contractor-1		Enter your full address*
Irrigation and Landscape		1234 Anystreet way
234-567-8910		Anytown
contractor@email.com		
contractor@ei		FL 12345
contractor@e	mail.com	FL 12345
contractor@ei Password Connect to o	ther controllers Search by Na	FL 12345 United States me, MAC, Phone, Address On Adive Delete On Manage Delete



HOMEOWNER Sharing Your Pro Ex 2.0 WiFi Controller

FROM NATIVE iOS/ANDROID App:

Download the K-Rain Pro EX WiFi App from the itunes or Google Play App Store.



itunes (iOS App

Google Play Android App



Complete the homeowner and contractor information cards included and give the card to your contractor.

Email share method:

If you have email set up on your smart phone, you can share your controller by tapping "Share" in the App on the Account Page.

Tap "Share Controller" and enter contractor's email address from the completed information card. Tap "Share" underneath the email address field.



The App will generate a share file in an email and send it directly to the contractor.

WEBSITE METHOD:

Go to **myproex.krain.com** and log into your account. In the "My Account" page. Click "Share" next to your controller and then save. The contractor will then be able to add your irrigation controller to their account based on the information documented (MAC Address) during controller installation.

	Ay account details
Mr. Smith	Enter your full address*
Homeowner	1234 Anystreet way
234-567-8910	Anytown
homeowner@email.com	FL 12345
Password	United States







K-Rain Manufacturing Corp.

1640 Australian Avenue Riviera Beach, FL 33404 USA 561.844.1002 FAX: 561.842.9493

1.800.735.7246 | www.krain.com