



The Pro-LC Controller is designed for residential and commercial applications.

Feature-packed, user-friendly and now a WiFi-ready controller.

The PRO-LC is available in 4, 8 and 12 stations and in indoor and outdoor models. Add the new 3100-BRIDGE (sold separately) and this feature-packed controller can be managed from your smart device using WiFi technology. Other user-friendly feature:

- Easy to follow programming
- A full program screen display listing watering days, number of start times, number of stations and special programming
- Large LCD display; rain/freeze sensor compatibility
- Lighting feature allows you to create a start time and run time to operate a lighting system.
- Weather IQ® uses local weather conditions to bypass the irrigation schedule in wet conditions
- Seasonal adjust for water conservation
- A buried valve locator for easy maintenance



Bridge WiFi Module





K-Rain Manufacturing Corp. 1640 Australian Avenue Riviera Beach, FL 33404 USA 561.844.1002 FAX: 561.842.9493

1.800.735.7246 | www.krain.com



Features and Benefits

- Easy to follow programming
- Large LCD display
- Patented full program display feature shows watering days, number of start times, number of stations and special programming
- Rain sensor and rain/freeze sensor ready Allows automated operation to be controlled by sensor station by station.
- Lighting feature allows you to create a start time and run time to operate a lighting system.
- Weather IQ® uses local weather conditions to bypass the irrigation schedule in wet conditions
- Seasonal adjust
- Buried valve locator
- Built-in Level Makes leveling the unit easy

Models

OUTDOOR MODELS

3104W 4 station, 110V AC internal transformer

3104W-P 4 station, 110V AC internal transformer with pigtail

3104W-220 4 station, 220V AC internal transformer 3108W 8 station, 110V AC internal transformer

3108W-P 8 station, 110V AC internal transformer with pigtail

3108W-220 8 station, 220V AC internal transformer 3112W 12 station, 110V AC internal transformer

3112W-P 12 station, 110V AC internal transformer with pigtail

3112W-220 12 station, 220V AC internal transformer

INDOOR MODELS

3104WID 4 station, 110V AC plug pack transformer
3104WID-220 4 station, 220V AC plug pack transformer
3108WID 8 station, 110V AC plug pack transformer
3108WID-220 8 station, 220V AC plug pack transformer
3112WID 12 station, 110V AC plug pack transformer
3112WID-220 12 station, 220V AC plug pack transformer

Specifications

OPERATING SPECIFICATIONS

- Station Run Times:1 minute to 6 hours
- Number of Programs: 3
- Number of Automatic Start Times:4 per program
- Program Watering Schedules:
 Odd (odd calendar days),
 Even (even calendar days),
 Custom (day of the week)

ELECTRICAL SPECIFICATIONS

- Power Input: 110V AC, 50/60Hz 240V AC, 50/60Hz
- Power Output: 24V AC 1.0Amp
- Power Backup: Lithium coin-cell battery maintains time and date during primary power outages.

DIMENSIONS

Height: 7" (17,8 cm)Width: 7" (17,8 cm)Depth: 3.5" (8,9 cm)

ACCESSORIES

- 3100-BRIDGE WiFi Module
- 3208-HRS Hardwired Rain Sensor
- 3208-HRFS Hardwired Rain/Freeze Sensor
- 3208-UWRFS Universal Wireless Rain/Freeze Sensor

